## NSN 5305-01-657-3919

**Thread Class:** 

Right-hand **Thread Length:**0.530 inches

**Thread Direction:** 

Fastener Length:

0.718 inches **Head Style:** 

За

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-657-3919

Flat countersunk
Head Diameter:
0.3206 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Point Length:
0.108 inches
Single Shear Strength:
95 pounds per square inch
Point Style:
Flat
Internal Drive Style:
Offset cruciform (torque set)
End Application:
C-17a globemaster iii
Thread Diameter:
0.181 inches
Grip Length:
0.188 inches
Thready Qty Per Inch (tpi):
32
Countersink Angle:
Between 129.0 degrees and 131.0 degrees
Surface Finish:
32.0 microinches threads
Point Chamfer Angle:
Between 25.0 degrees and 35.0 degrees
Product Name:
Screw, machine-130 degrees fl hd, ti, align pt
Special Features:
95 ksi min ultimate shear
Material:
Titanium alloy uns r56400

## NSN 5305-01-657-3919

Close Tolerance Screw - Page 2 of 2



Material Specification:
-------------------------

Ams 4967 assn standard single material response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0