

View Online at <https://aerobasegroup.com/nsn/5306-00-003-0579>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.610 inches

Fastener Length:

Between 2.734 inches and 2.739 inches

Head Style:

Round w/wrench flats

Head Diameter:

1.523 inches

Head Height:

Between 0.140 inches and 0.150 inches

Width Between Flats:

1.438 inches

Shoulder Diameter:

Between 0.9925 inches and 0.9936 inches

Shoulder Length:

Between 2.124 inches and 2.129 inches

Shank Unthreaded Hole Diameter:

0.106 inches and 0.116 inches first hole

Concentric Hole Depth:

Between 1.909 inches and 1.914 inches

Concentric Hole Diameter:

Between 0.249 inches and 0.255 inches

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

46.0 rockwell c and 49.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.537 inches and 2.542 inches first hole

Product Name:

Navy special project

Material:

Steel

Material Specification:

G-1010, fsc-26512 mfr ref single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837 type 2 cl 1 military specification single treatment response

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.