

View Online at <https://aerobasegroup.com/nsn/5306-00-003-3884>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.375 inches

Fastener Length:

Between 5.452 inches and 5.457 inches

Head Style:

Hexagon extended washer

Head Height:

0.400 inches

Width Between Flats:

Between 0.553 inches and 0.564 inches

Extended Washer Diameter:

1.150 inches

Extended Washer Thickness:

0.200 inches

Shoulder Diameter:

0.745 inches first shoulder and 0.746 inches first shoulder

Shoulder Length:

4.921 inches first shoulder and 4.926 inches first shoulder

Shank Unthreaded Hole Diameter:

0.108 inches first hole and 0.113 inches first hole

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

46.0 rockwell c and 49.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.570 inches first hole and 4.575 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel comp d6ac

Material Specification:

Mil-s-8949 military specification single material response

Surface Treatment:

Nickel

Surface Treatment Specification:

Mil-c-26074, class 1 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-8949 spec.