

View Online at <https://aerobasegroup.com/nsn/5306-00-003-5274>

Thread Direction:

Right-hand

Thread Length:

Between 0.609 inches and 0.629 inches

Eye Inside Diameter:

Between 0.375 inches and 0.378 inches

Shoulder Thickness:

Between 0.100 inches and 0.160 inches

Shank Length:

Between 3.849 inches and 3.889 inches

Eye Stock Thickness:

Between 0.240 inches and 0.260 inches

Shoulder Diameter:

Between 0.865 inches and 0.885 inches

Overall Length:

Between 5.007 inches and 5.167 inches

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Distance From Center Of Eye To Shank End:

4.589 inches

Eye Outside Width:

Between 0.865 inches and 0.885 inches

Material:

Steel comp 4130

Material Specification:

Mil-s-6758 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 1 federal specification single treatment response

Style Designator:

Round, closed w/shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.