

View Online at <https://aerobasegroup.com/nsn/5306-00-003-5274>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.609 inches and 0.629 inches

**Eye Inside Diameter:**

Between 0.375 inches and 0.378 inches

**Shoulder Thickness:**

Between 0.100 inches and 0.160 inches

**Shank Length:**

Between 3.849 inches and 3.889 inches

**Eye Stock Thickness:**

Between 0.240 inches and 0.260 inches

**Shoulder Diameter:**

Between 0.865 inches and 0.885 inches

**Overall Length:**

Between 5.007 inches and 5.167 inches

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Distance From Center Of Eye To Shank End:**

4.589 inches

**Eye Outside Width:**

Between 0.865 inches and 0.885 inches

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 1 federal specification single treatment response

**Style Designator:**

Round, closed w/shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.