

View Online at <https://aerobasegroup.com/nsn/5306-00-003-6538>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.438 inches

**Fastener Length:**

Between 2.930 inches and 2.940 inches

**Head Style:**

Dished hexagon

**Head Height:**

0.188 inches

**Width Between Flats:**

Between 0.741 inches and 0.752 inches

**Shoulder Diameter:**

0.6226 inches first shoulder and 0.6232 inches first shoulder

**Shoulder Length:**

2.492 inches first shoulder and 2.502 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.759 inches first hole and 2.769 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel

**Material Specification:**

G-1010, fscm 26512 mfr ref single material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0