

View Online at <https://aerobasegroup.com/nsn/5306-00-003-9029>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.333 inches

**Fastener Length:**

Between 2.416 inches and 2.426 inches

**Head Style:**

Round w/wrench flats

**Head Diameter:**

0.800 inches

**Head Height:**

0.156 inches

**Width Between Flats:**

Between 0.678 inches and 0.690 inches

**Shoulder Diameter:**

Between 0.623 inches and 0.624 inches

**Shoulder Length:**

Between 1.979 inches and 1.989 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches and 0.116 inches first hole

**Concentric Hole Depth:**

1.810 inches

**Concentric Hole Diameter:**

Between 0.311 inches and 0.313 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.224 inches and 2.234 inches first hole

**Special Features:**

Cadmium plate concentric hole surface

**Material:**

Steel

**Material Specification:**

G-1010 fscm 26512 mfr ref single material response

**Surface Treatment:**

Cadmium head

**Style Designator:**

Concentric hole unthreaded

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0