## NSN 5306-00-003-9030

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-003-9030 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.609 inches and 0.619 inches **Fastener Length:** 2.400 inches **Head Style:** Hexagon **Head Height:** 0.315 inches Width Between Flats: Between 1.053 inches and 1.066 inches **Shoulder Diameter:** 0.7480 inches and 0.7490 inches first shoulder **Shoulder Length:** 1.719 inches and 1.729 inches first shoulder **Hole Diameter:** 0.075 inches **Thread Diameter:** 0.500 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 49.0 rockwell c **Hole Configuration Style:** Hexagon flats **Shoulder Shape:** Round first shoulder **Product Name:** Navy special project Material:

Steel comp 4340

**Material Specification:** 

Ams6487 assn standard single material response

## NSN 5306-00-003-9030

Shoulder Bolt - Page 2 of 2

Mil-std (military Standard):

Mil-c-8837 spec.



Surface Treatment:
Cadmium
Surface Treatment Specification:
Mil-c-8837 military specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0