## NSN 5306-00-003-9647

Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-003-9647



**Thread Class:** 2a **Thread Direction: Right-hand Thread Length:** Between 0.615 inches and 0.685 inches Fastener Length: Between 0.990 inches and 1.010 inches Head Style: Double hexagon w/hole **Head Height:** Between 0.260 inches and 0.270 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** Between 0.365 inches and 0.385 inches **Extended Washer Thickness:** Between 0.040 inches and 0.050 inches Hole Diameter: 0.042 inches **Thread Diameter:** 0.190 inches Grip Length: Between 0.317 inches and 0.375 inches **Hole Quantity:** 4 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating: 42.0 rockwell c and 46.0 rockwell c Hole Configuration Style: Hexagon flats Surface Finish: 63.0 microinches grip Material: Steel **Material Specification:** 

C50t22, fscm 07482 mfr ref single material response

## NSN 5306-00-003-9647

Machine Bolt - Page 2 of 2

Surface Treatment:

Nickel

Surface Treatment Specification:

Ams 2403 assn standard single treatment response

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

