

View Online at <https://aerobasegroup.com/nsn/5306-00-004-5084>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.750 inches and 0.810 inches

**Fastener Length:**

3.500 inches

**Head Style:**

Hexagon

**Head Height:**

0.219 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Shank Unthreaded Hole Diameter:**

0.094 inches first hole and 0.101 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 2.690 inches and 2.750 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.360 inches first hole

**Surface Finish:**

63.0 microinches grip

**Material:**

Steel comp 8740

**Material Specification:**

Ams 6322 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0