## NSN 5306-00-004-7044

Internally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-004-7044 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.241 inches **Fastener Length:** 2.137 inches **Head Style:** Round w/wrench flats **Head Diameter:** 0.750 inches **Head Height:** 0.063 inches Width Between Flats: Between 0.552 inches and 0.562 inches **Shoulder Diameter:** Between 0.4976 inches and 0.4981 inches **Shoulder Length:** 1.792 inches **Shank Unthreaded Hole Diameter:** 0.072 inches first hole and 0.077 inches first hole **Concentric Hole Depth:** 0.320 inches **Concentric Hole Diameter:** Between 0.195 inches and 0.201 inches **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Center: 2.012 inches first hole Material: Steel comp d6ac **Material Specification:** G-1013 comp d6ac 26512 mfr ref single material response **Surface Treatment:** Cadmium **Style Designator:** Concentric hole unthreaded

Unjf

**Thread Series Designator:** 

## NSN 5306-00-004-7044

Internally Relieved Body Bolt - Page 2 of 2



She	lf L	ife:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0