NSN 5306-00-005-0550

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-005-0550 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.356 inches and 0.438 inches **Fastener Length:** Between 1.976 inches and 1.996 inches **Head Style:** Dished hexagon **Head Height:** Between 0.189 inches and 0.204 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Grip Diameter:** Between 0.3733 inches and 0.3742 inches **Shank Unthreaded Hole Diameter:** 0.106 inches first hole and 0.116 inches first hole **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.438 inches and 1.454 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 36.0 rockwell c and 41.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 1.861 inches first hole and 1.891 inches first hole **Surface Finish:** 63.0 microinches grip **Special Features:** Retaining element in shank Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 4130 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

NSN 5306-00-005-0550

Close Tolerance Bolt - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0