

View Online at <https://aerobasegroup.com/nsn/5306-00-006-0509>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.610 inches

Fastener Length:

Between 3.928 inches and 3.933 inches

Head Style:

Round w/wrench flats

Head Diameter:

1.710 inches

Head Height:

Between 0.140 inches and 0.150 inches

Width Between Flats:

1.625 inches

Shoulder Diameter:

Between 1.1175 inches and 1.1186 inches

Shoulder Length:

Between 3.318 inches and 3.323 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Concentric Hole Depth:

Between 3.018 inches and 3.033 inches

Concentric Hole Diameter:

Between 0.499 inches and 0.506 inches

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

46.0 rockwell c and 49.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.731 inches first hole and 3.736 inches first hole

Material:

Steel

Material Specification:

G-1010 c0mp 4330v fscm 26512 mfr ref single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

-110c-8837 type 2 cl 1 military specification single treatment response

Style Designator:

Concentric hole unthreaded

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

spec.