

View Online at <https://aerobasegroup.com/nsn/5306-00-006-0526>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.346 inches and 0.356 inches

**Fastener Length:**

2.323 inches

**Head Style:**

Hexagon

**Head Height:**

0.120 inches

**Width Between Flats:**

Between 0.740 inches and 0.752 inches

**Shoulder Diameter:**

Between 0.4995 inches and 0.5000 inches

**Shoulder Length:**

Between 1.967 inches and 1.977 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Concentric Hole Depth:**

1.870 inches

**Concentric Hole Diameter:**

Between 0.186 inches and 0.192 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

46.0 rockwell c and 49.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.203 inches first hole

**Material:**

Steel

**Material Specification:**

G-1013, fscm 26512 mfr ref single material response

**Surface Treatment:**

Cadmium head

**Surface Treatment Specification:**

Qq-c-320 federal specification single treatment response grip

**Style Designator:**

Concentric hole unthreaded

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-p-8837 spec.