

View Online at <https://aerobasegroup.com/nsn/5306-00-006-0526>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.346 inches and 0.356 inches

Fastener Length:

2.323 inches

Head Style:

Hexagon

Head Height:

0.120 inches

Width Between Flats:

Between 0.740 inches and 0.752 inches

Shoulder Diameter:

Between 0.4995 inches and 0.5000 inches

Shoulder Length:

Between 1.967 inches and 1.977 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Concentric Hole Depth:

1.870 inches

Concentric Hole Diameter:

Between 0.186 inches and 0.192 inches

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

46.0 rockwell c and 49.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.203 inches first hole

Material:

Steel

Material Specification:

G-1013, fscm 26512 mfr ref single material response

Surface Treatment:

Cadmium head

Surface Treatment Specification:

Qq-c-320 federal specification single treatment response grip

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-p-8837 spec.