NSN 5306-00-006-1454

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-006-1454

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.663 inches and 0.766 inches |
| Fastener Length: |
| Between 0.734 inches and 0.766 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.365 inches and 0.375 inches |
| Head Height: |
| Between 0.244 inches and 0.250 inches |
| Hole Diameter: |
| 0.047 inches |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.250 inches |
| Width Across Flats: |
| Between 0.1875 inches and 0.1900 inches |
| Hole Quantity: |
| 6 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 170000 pounds per square inch |
| Hardness Rating: |
| 38.0 rockwell c and 45.0 rockwell c |
| Minimum Yield Strength: |
| 150000 pounds per square inch |
| Hole Configuration Style: |
| Round |
| Material: |
| Steel |
| Material Specification: |
| 66 federal standard single material response |
| Thread Series Designator: |
| Unjc |

NSN 5306-00-006-1454

Internal Wrenching Bolt - Page 2 of 2



Specification Data:

80205-nas1351 professional/industrial association standard

Specification Or Standard:

6 type

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0