## NSN 5306-00-007-6026

Shear Bolt - Page 1 of 2

Between 0.553 inches and 0.603 inches

Between 3.563 inches and 3.593 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5306-00-007-6026

Head Style:
Dished hexagon
Head Diameter:
0.203 inches
Head Height:
0.188 inches
Width Between Flats:
Between 0.553 inches and 0.564 inches
Hole Diameter:
0.070 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 2.990 inches and 3.010 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Hole Configuration Style:
Hexagon corners
Material:
Steel comp e4340 or steel comp 8740 or steel comp 4340
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response

## NSN 5306-00-007-6026

Shear Bolt - Page 2 of 2

A003b0



Thread Series Designator:
Unjf
Specification Data:
80205-nas6606 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: