

View Online at <https://aerobasegroup.com/nsn/5306-00-008-8971>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.334 inches

Fastener Length:

Between 1.957 inches and 1.967 inches

Head Style:

Hexagon

Head Height:

0.188 inches

Width Between Flats:

Between 0.865 inches and 0.877 inches

Shoulder Diameter:

Between 0.7476 inches and 0.7482 inches

Shoulder Length:

Between 1.519 inches and 1.529 inches

Shank Unthreaded Hole Diameter:

0.110 inches first hole and 0.115 inches first hole

Concentric Hole Depth:

1.480 inches

Counterbore Diameter:

0.740 inches

Counterbore Depth:

0.110 inches

Concentric Hole Diameter:

Between 0.196 inches and 0.201 inches

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.786 inches first hole and 1.796 inches first hole

Material:

Steel

Material Specification:

G-1010, fscm 26512 mfr ref single material response

Surface Treatment:

Cadmium

Style Designator:

Counterbore unthreaded

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0