

View Online at <https://aerobasegroup.com/nsn/5306-00-008-8971>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.334 inches

**Fastener Length:**

Between 1.957 inches and 1.967 inches

**Head Style:**

Hexagon

**Head Height:**

0.188 inches

**Width Between Flats:**

Between 0.865 inches and 0.877 inches

**Shoulder Diameter:**

Between 0.7476 inches and 0.7482 inches

**Shoulder Length:**

Between 1.519 inches and 1.529 inches

**Shank Unthreaded Hole Diameter:**

0.110 inches first hole and 0.115 inches first hole

**Concentric Hole Depth:**

1.480 inches

**Counterbore Diameter:**

0.740 inches

**Counterbore Depth:**

0.110 inches

**Concentric Hole Diameter:**

Between 0.196 inches and 0.201 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.786 inches first hole and 1.796 inches first hole

**Material:**

Steel

**Material Specification:**

G-1010, fscm 26512 mfr ref single material response

**Surface Treatment:**

Cadmium

**Style Designator:**

Counterbore unthreaded

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0