

View Online at <https://aerobasegroup.com/nsn/5306-00-008-8987>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.260 inches and 1.300 inches

Fastener Length:

Between 8.420 inches and 8.460 inches

Head Style:

Double hexagon extended washer

Head Height:

Between 0.395 inches and 0.415 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Extended Washer Diameter:

Between 0.820 inches and 0.840 inches

Extended Washer Thickness:

Between 0.065 inches and 0.085 inches

First Diameter From Head:

Between 0.3736 inches and 0.3740 inches

Second Diameter From Head:

Between 0.315 inches and 0.320 inches

Third Diameter From Head:

Between 0.3736 inches and 0.3740 inches

Fourth Diameter From Head:

Between 0.315 inches and 0.320 inches

Fifth Diameter From Head:

Between 0.3736 inches and 0.3740 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.400 inches and 0.440 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 3.800 inches and 3.840 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 4.180 inches and 4.260 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

Between 6.740 inches and 6.780 inches

Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter:

Between 7.120 inches and 7.200 inches

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Externally Relieved Body Diameter Quantity:

4

Material:

Steel comp xm-13

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0