

View Online at <https://aerobasegroup.com/nsn/5306-00-009-7616>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.339 inches

**Fastener Length:**

Between 3.324 inches and 3.329 inches

**Head Style:**

Round w/wrench flats chamfered

**Head Diameter:**

0.875 inches

**Head Height:**

0.125 inches

**Width Between Flats:**

0.688 inches

**Shoulder Diameter:**

Between 0.4965 inches and 0.4985 inches

**Shoulder Length:**

Between 2.985 inches and 2.990 inches

**Shank Unthreaded Hole Diameter:**

0.075 inches first hole and 0.080 inches first hole

**Concentric Hole Depth:**

2.860 inches

**Concentric Hole Diameter:**

Between 0.339 inches and 0.349 inches

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Hardness Rating:**

46.0 rockwell c and 49.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.184 inches first hole and 3.189 inches first hole

**Material:**

Steel

**Material Specification:**

G-1010 mfr ref single material response

**Surface Treatment:**

Chromium

**Surface Treatment Specification:**

Qq-c-320 federal specification single treatment response

**Style Designator:**

Concentric hole unthreaded

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0