Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-010-9161

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.750 inches |
| Fastener Length: |
| 5.000 inches |
| Head Style: |
| Square |
| Head Height: |
| Between 0.156 inches and 0.188 inches |
| Width Between Flats: |
| Between 0.362 inches and 0.372 inches |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| 4.250 inches |
| Features Provided: |
| Unfinished head |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 60000 pounds per square inch |
| Hardness Rating: |
| 70.0 rockwell b and 100.0 rockwell b |
| Minimum Yield Strength: |
| 36000 pounds per square inch |
| Material: |
| Steel |
| Material Specification: |
| Sae gr 1 assn standard single material response |
| Thread Series Designator: |
| Unc |
| Specification Or Standard: |
| 1 type |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| N |

No

NSN 5306-00-010-9161 Machine Bolt - Page 2 of 2

Fiig: A003b0

