

View Online at <https://aerobasegroup.com/nsn/5306-00-011-0193>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.660 inches

**Fastener Length:**

2.470 inches

**Head Style:**

Hexagon

**Head Height:**

0.190 inches

**Width Between Flats:**

0.562 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

1.810 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.232 inches first hole

**Material:**

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.