

View Online at <https://aerobasegroup.com/nsn/5306-00-012-0979>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.669 inches and 0.719 inches

Fastener Length:

Between 3.054 inches and 3.084 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.415 inches and 0.435 inches

Width Between Flats:

Between 0.494 inches and 0.503 inches

Extended Washer Diameter:

Between 0.740 inches and 0.750 inches

Extended Washer Thickness:

Between 0.089 inches and 0.109 inches

Hole Diameter:

0.055 inches

Grip Diameter:

Between 0.4360 inches and 0.4370 inches

Thread Diameter:

0.438 inches

Grip Length:

Between 2.365 inches and 2.385 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Hole Configuration Style:

Hexagon flats

Product Name:

Navy special project

Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas627 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.