NSN 5306-00-018-0084

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-018-0084 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.875 inches and 1.062 inches **Fastener Length:** Between 1.563 inches and 1.625 inches **Head Style:** Hexagon **Head Height:** Between 0.195 inches and 0.211 inches Width Between Flats: Between 0.489 inches and 0.500 inches **Thread Diameter:** 0.312 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 120000 pounds per square inch **Hardness Rating:** 23.0 rockwell c and 34.0 rockwell c Material: Steel comp 1050 or steel comp 1053 **Material Specification:** 66 federal standard all material responses **Surface Treatment:** Cadmium and chromate or zinc **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification 1st treatment response or qq-z-325 type 2 cl 2 federal specification 2nd treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 1 type and 5 grade Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5306-00-018-0084

Machine Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-1222 spec.