NSN 5306-00-018-7745

Assembled Washer Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-018-7745 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.619 inches and 0.719 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Hexagon **Head Height:** Between 0.172 inches and 0.190 inches Width Between Flats: Between 0.428 inches and 0.437 inches Washer Quantity: **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Primary Washer Outside Diameter:** Between 0.460 inches and 0.475 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.023 inches and 0.028 inches **Special Features:** W/header point Material: Steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1050 **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5306-00-018-7745

Assembled Washer Bolt - Page 2 of 2



Fiig:

A003b0