# NSN 5306-00-020-0376

Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-020-0376



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.713 inches and 0.733 inches

## Fastener Length:

0.812 inches

#### **Head Style:**

Double hexagon w/hole

**Head Height:** 

0.260 inches

Width Between Flats:

Between 0.243 inches and 0.251 inches

### **Extended Washer Diameter:**

0.375 inches

### **Extended Washer Thickness:**

Between 0.060 inches and 0.070 inches

Hole Diameter:

0.047 inches

**Thread Diameter:** 

0.250 inches

Grip Length:

Between 0.079 inches and 0.099 inches

### Hole Quantity:

4

Hole Type:

Drilled

**Features Provided:** 

Finished head

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

130000 pounds per square inch

Hardness Rating:

248.0 brinell standard and 341.0 brinell standard

Minimum Yield Strength:

85000 pounds per square inch

Hole Configuration Style:

Double hexagon longitudinal hole

Surface Finish:

32.0 microinches grip

# NSN 5306-00-020-0376

Machine Bolt - Page 2 of 2

Material:

Iron alloy 660

Material Specification:

Ams 5737 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

