
# NSN 5306-00-020-1118

Shear Bolt - Page 1 of 2



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.731 inches and 0.751 inches

#### Fastener Length:

2.616 inches

#### **Head Style:**

Double hexagon w/hole

**Head Height:** 

0.435 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

#### **Extended Washer Diameter:**

Between 0.740 inches and 0.750 inches

#### **Extended Washer Thickness:**

0.099 inches

## Grip Diameter:

Between 0.4360 inches and 0.4370 inches

# **Thread Diameter:**

0.438 inches

Grip Length:

Between 1.865 inches and 1.885 inches

## Thready Qty Per Inch (tpi):

20

## Min. Tensile Strength (psi):

180000 pounds per square inch

## Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

## Material:

Steel

## Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

# **Thread Series Designator:**

Unjf

Shelf Life:

N/a

# Unit Of Measure:

---



# NSN 5306-00-020-1118

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

