

View Online at <https://aerobasegroup.com/nsn/5306-00-020-3615>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.460 inches

**Fastener Length:**

1.030 inches

**Head Style:**

Dee

**Head Diameter:**

0.750 inches

**Head Height:**

Between 0.150 inches and 0.165 inches

**Distance From Centerline To Flat:**

0.240 inches

**Shank Unthreaded Hole Diameter:**

0.074 inches first hole and 0.081 inches first hole

**First Diameter From Head:**

Between 0.410 inches and 0.411 inches

**Second Diameter From Head:**

Between 0.400 inches and 0.401 inches

**Third Diameter From Head:**

Between 0.306 inches and 0.316 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.140 inches and 0.150 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.470 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

0.570 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

28.0 rockwell c and 32.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.910 inches first hole

**Externally Relieved Body Diameter Quantity:**

3

**Material:**

Steel comp 8740

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0