

View Online at <https://aerobasegroup.com/nsn/5306-00-020-3615>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.460 inches

Fastener Length:

1.030 inches

Head Style:

Dee

Head Diameter:

0.750 inches

Head Height:

Between 0.150 inches and 0.165 inches

Distance From Centerline To Flat:

0.240 inches

Shank Unthreaded Hole Diameter:

0.074 inches first hole and 0.081 inches first hole

First Diameter From Head:

Between 0.410 inches and 0.411 inches

Second Diameter From Head:

Between 0.400 inches and 0.401 inches

Third Diameter From Head:

Between 0.306 inches and 0.316 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.140 inches and 0.150 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

0.470 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

0.570 inches

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

28.0 rockwell c and 32.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.910 inches first hole

Externally Relieved Body Diameter Quantity:

3

Material:

Steel comp 8740

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0