## NSN 5306-00-021-4923

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-021-4923

View Online at https://aerobasegroup.com/nsn/5306-00-021-4923
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.288 inches and 0.318 inches
Fastener Length:
Between 1.905 inches and 1.925 inches
Head Style:
Tee no. 6
Head Height:
Between 0.240 inches and 0.260 inches
Head Length:
Between 0.745 inches and 0.755 inches
Width Between Flats:
Between 0.550 inches and 0.560 inches
Shoulder Diameter:
0.452 inches first shoulder and 0.453 inches first shoulder
Shoulder Length:
1.431 inches first shoulder and 1.440 inches first shoulder
Shank Unthreaded Hole Diameter:
0.065 inches first hole and 0.072 inches first hole
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Hardness Rating:
35.0 rockwell c and 40.0 rockwell c
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.525 inches first hole and 1.565 inches first hole
Chamfer Angle:
Between 43.0 degrees and 47.0 degrees
Shoulder Shape:
Round first shoulder
Material:
Steel comp 615
Material Specification:
Ams 5616 assn standard single material response or ams 7470 assn standard single material response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## **NSN 5306-00-021-4923** Shoulder Bolt - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

Demilitarization:

No

Fiig:

A003b0