
NSN 5306-00-022-2002

Machine Bolt - Page 1 of 2

2a

18





Thread Class: Thread Direction: Right-hand Thread Length: Between 1.107 inches and 1.218 inches Fastener Length: Between 1.218 inches and 1.282 inches **Head Style:** Hexagon **Head Height:** Between 0.375 inches and 0.390 inches Width Between Flats: Between 0.798 inches and 0.812 inches Locking Feature: Distortions bearing surface of head **Thread Diameter:** 0.562 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 95000 pounds per square inch Hardness Rating: 96.0 rockwell b and 104.0 rockwell b **Minimum Yield Strength:** 85000 pounds per square inch Material: Steel comp 1035 Material Specification: Qq-634 federal specification single material response Surface Treatment: Cadmium or zinc Surface Treatment Specification: Qq-p-416, type 1 cl 2 federal specification 1st treatment response or qq-a-325, type 1 cl2 federal specification 2nd treatment response **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure:

NSN 5306-00-022-2002

Machine Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

