

View Online at <https://aerobasegroup.com/nsn/5306-00-023-7136>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.500 inches

**Fastener Length:**

2.150 inches

**Head Style:**

Hexagon

**Head Height:**

0.250 inches

**Width Between Flats:**

1.063 inches

**Shoulder Diameter:**

0.7150 inches first shoulder

**Shoulder Length:**

1.647 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.110 inches first hole

**Thread Diameter:**

0.500 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.922 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 4340

**Material Specification:**

Mil-s-5000, cond c4 military specification single material response

**Surface Treatment:**

Chromium grip

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.