## NSN 5306-00-032-5633

Shear Bolt - Page 1 of 2

Between 0.790 inches and 0.840 inches

Between 2.050 inches and 2.080 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5306-00-032-5633

Head Style:
Double hexagon w/hole
Head Height:
0.464 inches
Width Between Flats:
Between 0.553 inches and 0.564 inches
Extended Washer Diameter:
Between 0.820 inches and 0.830 inches
Extended Washer Thickness:
0.083 inches
Hole Diameter:
0.124 inches
Grip Diameter:
Between 0.4360 inches and 0.4370 inches
Thread Diameter:
0.438 inches
Grip Length:
Between 1.240 inches and 1.260 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
260000 pounds per square inch
Hole Configuration Style:
Hexagon longitudinal hole
Material:
Steel
Material Specification:
Stsbs003 fscm 98897 mfr ref single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Stsbs003 fscm 98897 mfr ref single treatment response
Thread Series Designator:
Unjf

## NSN 5306-00-032-5633

Shear Bolt - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0