## NSN 5306-00-032-7654

Machine Bolt - Page 1 of 2

Uns



View Online at https://aerobasegroup.com/nsn/5306-00-032-7654

| view Offiline at https://aerobasegroup.com/hist//3500-00-052-7054  |
|--|
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.281 inches   |
| Fastener Length:   |
| 0.560 inches   |
| Head Style:  |
| Hexagon  |
| Head Height:   |
| 0.154 inches   |
| Width Between Flats:   |
| 0.375 inches   |
| Hole Diameter:   |
| 0.062 inches   |
| Thread Diameter:   |
| 0.250 inches   |
| Grip Length:   |
| 0.125 inches   |
| Hole Quantity:   |
| 1  |
| Hole Type:   |
| Drilled  |
| Features Provided:   |
| Finished head  |
| Nonstandard Thread Pitch Diameter:   |
| +0.2149 to 0.2175 inches   |
| Thready Qty Per Inch (tpi):  |
| 20   |
| Min. Tensile Strength (psi):   |
| 194000 pounds per square inch  |
| Hardness Rating:   |
| 38.0 rockwell c and 42.0 rockwell c  |
| Hole Configuration Style:  |
| Hexagon flats  |
| Material:  |
| Steel comp 4140 or steel comp 8740 or steel comp 416f  |
| Material Specification:  |
| Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 5610 assn standard |
| 3rd material response  |
| Surface Treatment:   |
| Cadmium  |
| Thread Series Designator:  |

## NSN 5306-00-032-7654

Machine Bolt - Page 2 of 2



| Shelf | Life: |
|-------|-------|
| N/a   |       |
| 11!(  | SC 84 |

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.