Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-034-3064

Thread Class:
3a
Thread Length:
0.590 inches
Fastener Length:
2.250 inches
Head Style:
Hexagon
Head Height:
0.220 inches
Shank Unthreaded Hole Diameter:
0.079 inches first hole and 0.084 inches first hole
First Diameter From Head:
Between 0.372 inches and 0.373 inches
Second Diameter From Head:
Between 0.310 inches and 0.315 inches
Third Diameter From Head:
Between 0.372 inches and 0.373 inches
Fourth Diameter From Head:
0.315 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.190 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
0.660 inches
Distance From Largest Bearing Surface Of Head To End Of Third Diameter:
1.040 inches
Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:
1.660 inches
Thread Diameter:
0.375 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
175000 pounds per square inch
Distance From Head Largest Bearing Surface To Shank Hole Center:
2.126 inches first hole
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

NSN 5306-00-034-3064

Externally Relieved Body Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

