NSN 5306-00-035-5425

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-035-5425

Thread Class:				
3a				
Thread Direction:				
Right-hand				
Thread Length:				
Between 0.788 inches and 0.838 inches				
Fastener Length:				
Between 1.923 inches and 1.953 inches				
Head Style:				
Double hexagon w/hole				
Head Height:				
Between 0.425 inches and 0.445 inches				
Width Between Flats:				
Between 0.492 inches and 0.502 inches				
Extended Washer Diameter:				
Between 0.740 inches and 0.750 inches				
Extended Washer Thickness:				
Between 0.089 inches and 0.109 inches				
Hole Diameter:				
0.055 inches				
Grip Diameter:				
Grip Diameter: Between 0.4360 inches and 0.4370 inches				
•				
Between 0.4360 inches and 0.4370 inches				
Between 0.4360 inches and 0.4370 inches Thread Diameter:				
Between 0.4360 inches and 0.4370 inches Thread Diameter: 0.438 inches				
Between 0.4360 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length:				
Between 0.4360 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 1.115 inches and 1.135 inches				
Between 0.4360 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 1.115 inches and 1.135 inches Hole Quantity:				
Between 0.4360 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 1.115 inches and 1.135 inches Hole Quantity:				
Between 0.4360 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 1.115 inches and 1.135 inches Hole Quantity: 4 Hole Type:				
Between 0.4360 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 1.115 inches and 1.135 inches Hole Quantity: 4 Hole Type: Drilled				
Between 0.4360 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 1.115 inches and 1.135 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi):				
Between 0.4360 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 1.115 inches and 1.135 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 20				
Between 0.4360 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 1.115 inches and 1.135 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi):				
Between 0.4360 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 1.115 inches and 1.135 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch				
Between 0.4360 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 1.115 inches and 1.135 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating:				
Between 0.4360 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 1.115 inches and 1.135 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c				
Between 0.4360 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 1.115 inches and 1.135 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c Hole Configuration Style:				

Material Specification:
Ams 6487 assn standard single material response

NSN 5306-00-035-5425

Shear Bolt - Page 2 of 2



	tment:

Cadmium and dichromate

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0