## NSN 5306-00-038-2634

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-038-2634 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.743 inches and 1.823 inches **Fastener Length:** Between 3.609 inches and 3.657 inches **Head Style:** Hexagon extended washer **Head Height:** Between 0.499 inches and 0.563 inches Width Between Flats: Between 0.553 inches and 0.563 inches **Extended Washer Diameter:** 0.812 inches **Extended Washer Thickness:** Between 0.296 inches and 0.328 inches **Thread Diameter:** 0.562 inches **Grip Length:** Between 1.834 inches and 1.866 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 125000 pounds per square inch Surface Finish: 104.0 microinches Material: Stainless steel **Material Specification:** Mil-s-6758, cond f military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 federal specification single treatment response **Thread Series Designator:** 

Unf

Shelf Life:

N/a

## NSN 5306-00-038-2634

Machine Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.