
NSN 5306-00-040-9594

Machine Bolt - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.638 inches and 0.688 inches Fastener Length: Between 2.023 inches and 2.053 inches **Head Style:** Hexagon **Head Height:** Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.554 inches and 0.564 inches Hole Diameter: 0.070 inches **Thread Diameter:** 0.375 inches Grip Length: Between 1.365 inches and 1.385 inches **Hole Quantity:** Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 140000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Iron alloy 660 **Material Specification:** Ams 5735 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5733 assn standard 2nd material response Surface Treatment: Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unf

1

NSN 5306-00-040-9594

Machine Bolt - Page 2 of 2



Specification Data:

80205-nas1006 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0