NSN 5306-00-044-5054



Ribbed Shoulder Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-044-5054 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.750 inches **Fastener Length:** 1.750 inches **Head Style:** Flat chamfer **Head Diameter:** 0.760 inches **Head Height:** 0.280 inches **Shoulder Diameter:** 0.458 inches first shoulder **Shoulder Length:** 0.810 inches first shoulder **Rib Major Diameter:** Between 0.487 inches and 0.497 inches Rib Length: 0.630 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.060 inches **Rib Minor Diameter:** 0.458 inches **Rib Quantity:** 36 **Thread Diameter:** 0.437 inches Thready Qty Per Inch (tpi): **Rib Included Angle:** 80.0 degrees **Shoulder Shape:**

Ribbed first shoulder Material: Steel **Material Specification:** Sae gr 8 assn standard single material response **Surface Treatment:** Cadmium and chromate

NSN 5306-00-044-5054

Ribbed Shoulder Bolt - Page 2 of 2



Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A003b0