NSN 5306-00-045-1975

Assembled Washer Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-045-1975

| View Online at https://aerobasegroup.com/nsn/53 |
|---|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.750 inches |
| Fastener Length: |
| 0.750 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.208 inches and 0.230 inches |
| Width Between Flats: |
| Between 0.489 inches and 0.500 inches |
| Washer Quantity: |
| 1 |
| Thread Diameter: |
| 0.312 inches |
| Thready Qty Per Inch (tpi): |
| 18 |
| Primary Washer Outside Diameter: |
| Between 0.540 inches and 0.556 inches |
| Primary Washer Material Thickness: |
| 0.078 inches |
| Material: |
| Steel comp 1010 or steel comp 1020 |
| Material Specification: |
| Astm a108 assn standard all material responses |
| Surface Treatment: |
| Cadmium or zinc |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |