## NSN 5306-00-047-3436

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-047-3436 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.635 inches and 0.655 inches **Fastener Length:** 1.395 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.388 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Extended Washer Diameter:** Between 0.639 inches and 0.649 inches **Extended Washer Thickness:** 0.091 inches **Hole Diameter:** 0.055 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.740 inches and 0.760 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c **Hole Configuration Style:** Hexagon longitudinal hole Material:

Steel **Surface Treatment:** Cadmium and chromate

## NSN 5306-00-047-3436

Shear Bolt - Page 2 of 2



Surface	Treatment	Specification:
Juliace	HEAUHEIL	opecilication.

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0