## NSN 5306-00-051-7182

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-051-7182 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.436 inches and 0.515 inches **Fastener Length:** Between 0.640 inches and 0.687 inches **Head Style:** Hexagon **Head Height:** Between 0.140 inches and 0.172 inches Width Between Flats: Between 0.428 inches and 0.440 inches **Hole Diameter:** 0.046 inches **Grip Diameter:** Between 0.2487 inches and 0.2492 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.172 inches and 0.204 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** 26.0 rockwell c and 32.0 rockwell c **Hole Configuration Style:** Hexagon flats **Surface Finish:** 63.0 microinches grip Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response

Surface Treatment:

**Passivate** 

## NSN 5306-00-051-7182

Close Tolerance Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Mil-std (military Standard):

Mil-s-18732 spec.