NSN 5306-00-051-9282

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-051-9282 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.355 inches **Fastener Length:** 3.685 inches **Head Style:** Hexagon **Head Height:** 0.327 inches Width Between Flats: 0.940 inches **Hole Diameter:** 0.062 inches **Shank Unthreaded Hole Diameter:** 0.110 inches first hole **First Diameter From Head:** 0.624 inches **Second Diameter From Head:** 0.443 inches **Third Diameter From Head:** 0.624 inches **Fourth Diameter From Head:** 0.427 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.845 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 4.155 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 6.030 inches **Thread Diameter:** 0.500 inches **Hole Quantity:** Hole Type: Drilled

20

Thready Qty Per Inch (tpi):

NSN 5306-00-051-9282 Externally Relieved Body Bolt - Page 2 of 2



Hole Configuration Style:
Hexagon flats
Distance From Head Largest Bearing Surface To Shank Hole Center:
6.247 inches first hole
Externally Relieved Body Diameter Quantity:
1
Material:
Steel
Surface Treatment:
Cadmium
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0