NSN 5306-00-052-3714

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-052-3714

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.500 inches |
| Fastener Length: |
| 2.500 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| 0.375 inches |
| Width Between Flats: |
| 0.750 inches |
| End Application: |
| Loader, scoop type; ded 4/4 w/4 1-1/2 or 5 cy gp bucket (cce) |
| Thread Diameter: |
| 0.500 inches |
| Grip Length: |
| 1.000 inches |
| Features Provided: |
| Finished head |
| |
| Thready Qty Per Inch (tpi): |
| |
| Thready Qty Per Inch (tpi): |
| Thready Qty Per Inch (tpi): 20 |
| Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch |
| Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): |
| Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: |
| Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 40.0 rockwell c and 43.0 rockwell c |
| Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 40.0 rockwell c and 43.0 rockwell c Special Features: |
| Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 40.0 rockwell c and 43.0 rockwell c Special Features: Color black Material: |
| Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 40.0 rockwell c and 43.0 rockwell c Special Features: Color black Material: Steel comp 4140 |
| Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 40.0 rockwell c and 43.0 rockwell c Special Features: Color black Material: Steel comp 4140 Material Specification: |
| Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 40.0 rockwell c and 43.0 rockwell c Special Features: Color black Material: Steel comp 4140 Material Specification: Sae assn standard single material response |
| Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 40.0 rockwell c and 43.0 rockwell c Special Features: Color black Material: Steel comp 4140 Material Specification: Sae assn standard single material response Surface Treatment: |
| Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 40.0 rockwell c and 43.0 rockwell c Special Features: Color black Material: Steel comp 4140 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium |
| Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 40.0 rockwell c and 43.0 rockwell c Special Features: Color black Material: Steel comp 4140 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Thread Series Designator: |
| Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 40.0 rockwell c and 43.0 rockwell c Special Features: Color black Material: Steel comp 4140 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Thread Series Designator: Unf |
| Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 40.0 rockwell c and 43.0 rockwell c Special Features: Color black Material: Steel comp 4140 Material Specification: Sae assn standard single material response Surface Treatment: Cadmium Thread Series Designator: |

--

NSN 5306-00-052-3714

Machine Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0