

View Online at <https://aerobasegroup.com/nsn/5306-00-053-8792>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.812 inches and 0.872 inches

**Fastener Length:**

Between 1.702 inches and 1.732 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.265 inches and 0.297 inches

**Width Between Flats:**

Between 0.741 inches and 0.751 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Thread Diameter:**

0.500 inches

**Grip Length:**

Between 0.860 inches and 0.890 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.474 inches first hole and 1.494 inches first hole

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5002 spec.