

View Online at <https://aerobasegroup.com/nsn/5306-00-054-3631>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.788 inches and 0.838 inches

**Fastener Length:**

Between 1.548 inches and 1.578 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.454 inches and 0.474 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Extended Washer Diameter:**

Between 0.820 inches and 0.830 inches

**Extended Washer Thickness:**

Between 0.073 inches and 0.093 inches

**Grip Diameter:**

Between 0.4360 inches and 0.4370 inches

**Thread Diameter:**

0.438 inches

**Grip Length:**

Between 0.740 inches and 0.760 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Material:**

Steel

**Material Specification:**

Bacb30cx, fscm 81205 mfr ref single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas 672 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0