NSN 5306-00-054-5674

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-054-5674

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.594 inches and 0.644 inches
Fastener Length:
Between 1.166 inches and 1.196 inches
Head Style:
Double hexagon extended washer
Head Height:
Between 0.378 inches and 0.398 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Extended Washer Diameter:
Between 0.639 inches and 0.649 inches
Extended Washer Thickness:
Between 0.081 inches and 0.101 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 0.552 inches and 0.572 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Surface Finish:
32.0 microinches grip
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas626 professional/industrial association standard

NSN 5306-00-054-5674

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

