NSN 5306-00-055-7536

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-055-7536

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.741 inches |
| Fastener Length: |
| 1.366 inches |
| Head Style: |
| Double hexagon w/hole |
| Head Height: |
| 0.504 inches |
| Width Between Flats: |
| Between 0.556 inches and 0.565 inches |
| Extended Washer Diameter: |
| 0.823 inches |
| Extended Washer Thickness: |
| 0.123 inches |
| Grip Diameter: |
| Between 0.4985 inches and 0.4995 inches |
| Thread Diameter: |
| 0.500 inches |
| Grip Length: |
| 0.625 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Hardness Rating: |
| 39.0 rockwell c and 43.0 rockwell c |
| Material: |
| Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150 |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Nas-672 assn standard single treatment response |
| Thread Series Designator: |
| Unf |
| Specification Data: |
| 80205-nas628 professional/industrial association standard |
| Shelf Life: |

N/a

NSN 5306-00-055-7536

Shear Bolt - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A003b0