

View Online at <https://aerobasegroup.com/nsn/5306-00-055-7536>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.741 inches

**Fastener Length:**

1.366 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.504 inches

**Width Between Flats:**

Between 0.556 inches and 0.565 inches

**Extended Washer Diameter:**

0.823 inches

**Extended Washer Thickness:**

0.123 inches

**Grip Diameter:**

Between 0.4985 inches and 0.4995 inches

**Thread Diameter:**

0.500 inches

**Grip Length:**

0.625 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Material:**

Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas-672 assn standard single treatment response

**Thread Series Designator:**

Unf

**Specification Data:**

80205-nas628 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0